## **Aerial Lift Safety Training Vernon**

Aerial Lift Safety Training Vernon - There are roughly 26 to 30 construction fatalities in North America due to the utilization of aerial lifts. Nearly all of the individuals killed are craftsmen like for example painters, electrical workers, laborers, ironworkers or carpenters. Most deaths are caused by electrocutions, falls and tip-overs. The greatest hazard is from boom-supported lifts, such as cherry pickers and bucket trucks. Nearly all fatalities are related to this type of lift, with the rest involving scissor lifts. Other risks comprise being struck by falling objects, being thrown out of a bucket, and being caught between the guardrail or lift bucket and a thing, such as a joist or steel beam.

In order to operate an aerial lift safely, carry out an inspection on the following things before using the device: emergency and operating controls, safety devices (like for instance, guardrails and outriggers), personal fall protection gear, and wheels and tires. Check for possible leaks in the air, fuel-system, hydraulic fluid. Check the device for loose or missing parts.

The area where the device will be used must be thoroughly checked for potential hazards, like for instance holes, bumps, drop-offs and debris. Overhead power lines must be avoided or closely monitored. It is suggested that aerial lift devices be used on surfaces that are stable and level. Don't work on steep slopes that go beyond slope limitations specified by the manufacturer. Even on a level slope, wheel chocks, outriggers and brakes should be set.

Employers are needed to provide maintenance mechanics and aerial lift operators with the correct instruction manuals. Mechanics and operators should be trained by a licensed person experienced with the relevant aerial lift model.

## Aerial Lift Safety Tips:

- o Prior to operating, close lift platform chains and doors.
- o Climbing on and leaning over guardrails is prohibited. Stand on the platform or floor of the bucket.
- o Make use of the provided manufacturer's load-capacity limits.
- o When working near traffic, utilize right work-zone warnings, like for instance cones and signs.

Electrocutions are preventable if safety procedures are followed. Stay well away from power lines - at least 10 feet. Qualified electrical workers must de-energize and/or insulate power lines. Those working should utilize personal protective equipment and tools, like for instance a bucket which is insulated. Then again, an insulated bucket does not protect from electrocution if, for instance, the worker touches another wire providing a path to the ground.

When inside the bucket, workers should prevent possible falls by securing themselves to the guardrails by using a full-body harness or a positioning device. If there is an anchorage within the bucket, a positioning belt along with a short lanyard is acceptable.

By following the manufacturer's directions, tip-overs could be prevented. Never drive the lift platform when it is elevated, unless otherwise specified by the manufacturer. Adhere to the vertical and horizontal reach limits of the device, and never exceed the specified load-capacity.